

MAC 3000 Mesa de acristalar STRONG BULL



El modelo MAC 3000 de Strong Bull esta diseñado y fabricado para el montaje vertical del vidrio, es decir acristalamiento en carpintería de Aluminio y PVC.

- Tamaño alto min. /máx. carpinterías 0/2800 mm.
- Tamaño ancho min. /máx. carpinterías (apertura) 70/3000 mm.
- Recorrido de prensado 60 mm.

- Capacidad de carga / 150 Kg. a 7bar.
- Recorrido de elevación 550 mm.
- Fuerza de apriete min./máx. 10/100 Kg
- Peso aprox. de la máquina 675 Kg.
- Garantía de paralelismo/perpendicular mediante cremalleras.
- Presión de la línea de aire (min. /máx.) De 5 a 8 bares.
- Velocidad de movimiento columna Manual.
- Fuerza de apriete min. /máx. 10/100Kg.

- Size high min. / max. carpentry 0/2800 mm.
- Size min. / max. carpentry (opening) 70/3000 mm.
- Press stroke 60 mm.
- Load capacity / 150 Kg. To 7bar.
- Lifting stroke 550 mm.
- Tightening force min./max. 10/100 Kg
- Weight approx. of the machine 675 Kg.
- Guarantee of parallelism / perpendicular by means of zips.
- Pressure of the air line (min./max.) 5 to 8 bar.
- Manual column movement speed.
- Tightening force min. / max. 10 / 100Kg.

SKU: e785433fcacc